



# BERTH 511

MAX DRAUGHT (MW):	11.5 M	MAX/MIN MANIFOLD HEIGHT	
MAX LOA:	200 M	ABOVE WATERLINE (MW):	17.6/3.2 M
MAX BREADTH:	N/A	QUAY DECK HEIGHT (MW):	3.5 M
UKC:	0.5 M	MAX BCM/SCM:	103 M
MIN. PARALLEL BODY**:	45 M	MAX DISPLACEMENT:	N/A
MIN. FREEBOARD (MW):	N/A	MAX SPEED:	N/A


\*\* Min. parallel body, 45 m, of which at least 32 m needs to be from ship's connected manifold to stern or forward depending on side alongside.



- MANIFOLD
  - DOLPHIN
  - FENDER
  - HOOK (h)
  - BOLLARD
  - EMERGENCY EXIT
  - CoM CENTER of MANIFOLD
- } SWL = Safe Working Load in tons

	 N	BERTH DIRECTION 033° / 213°	<b>MOORING PLAN SKARVIK BERTH 511</b>			BERTH / DRAWING NO BERTH511	APPROVED BY CL
		REV. DATE / DATE 2019-10-04	DRAWN MAFLOBE/	SCALE /			

PRODUCT	COMPANY	MAX PRESSURE BAR	MAX LOADING/DISCHARGING CAPACITY M3/H	SIZE OF CONN.	No.
---------	---------	------------------	---------------------------------------	---------------	-----






Hard arm connections: 8", 10", 12" with 150 lbs  
Hose connections: ≤ 6"

- ① = Hard arm No.
- = Hard arm symbol
- = Hose symbol


Bunkers available by barge  
Fresh water available  
Maximum 2 hoses to be used  
per ship/shore connection

	 N	BERTH DIRECTION 033° / 213°	<b>MANIFOLD ARRANGEMENT SKARVIK BERTH 511</b>			BERTH / DRAWING NO BERTH511	APPROVED BY CL
			REV. DATE /DATE 2020-06-10	DRAWN MAFLOBE	SCALE /		



- ① Loading arm No.
- VRU/VDU Connection
- BOLLARD
- ☞ HOOK
- FENDER

CoM CENTRE of MANIFOLD



### BERTH 511 SKARVIKSHAMNEN SIDE VIEW



BERTH DIRECTION  
017°/197°

REV. DATE / DATE  
2020-06-08

DRAWN  
MAFLOBE

SCALE

BERTH / DRAWING NO  
BERTH511sideview

APPROVED BY  
CL